



AIR GUARD CONTROL CSA PUFFER IV MODEL (2007) INSTRUCTIONS

- 1. Open the dispenser Door.** Pull up on the top of the Housing and pull the Door towards you.
- 2. Remove the Battery Cap.** Remove the Cap by turning it counter-clockwise. It only turns about 1/8 of a turn and then you can pull it straight off. Be sure there are no batteries inside.
- 3. Select the mode of operation.** If the 12/24 Hour Mode Switch is on "12HR", the unit will spray every 15 minutes between the hours of 5 PM and 5 AM. If the 12/24 Hour Mode Switch is on "24HR", the unit will spray every 30 minutes 24 hours a day. Move the 12/24 Hour Mode Switch to the desired mode of operation. Moving the switch "up" will put the unit in 12 Hour Mode and moving it "down" will put the unit in 24 Hour Mode.
- 4. Make sure the Power Slide Switch is in the "OFF" position.** Slide the covered switch downward.
- 5. Install batteries.** Install (4) D-cell alkaline batteries as shown on label in battery compartment. Use only all new batteries.
- 6. Install and tighten Battery Cap.** Line up the tabs; the cap only goes on one way.
- 7. Turn Power Slide Switch to "ON" position.** Unit will cycle the motor (test spray). Anytime the switch is turned off, then on, it will test spray immediately. **Caution: Keep clear of the spray nozzle (actuator) whenever a can is present.**
- 8. Press Reset Button.** Unit will cycle the motor (test sprays).
- 9. Set time.** Press the "clock" key to select hours or minutes and using "set" key to advance the count of either.
- 10. Load can.** Turn the power slide switch "OFF". Be sure that the Hammer is in the up position and push it up with finger if it is not. Install the aerosol can by sliding it into the Can Collar (metal bracket) while aligning the actuator.
- 11. POINT THE UNIT AWAY FROM YOU.** Turn the slide switch "ON". The unit will test spray.
- 12. Close the door.** Make sure that the spray nozzle (actuator) is placed properly to spray out of the door opening.
- 13. Place unit into service.**

Use caution as the unit will now spray automatically once every 15 minutes between the hours of 5 PM and 5 AM or once every 30 minutes 24 hours a day, depending on the 12/24 Hour Mode Switch position.

CAUTION: When replacing batteries, be sure that slide switch is in the "OFF" position.

When placing the unit in storage:

1. Clean the outside of the unit.
2. Remove the batteries.
3. Open the unit and remove the aerosol can.
4. Close the unit.
5. Store the Puffers in a dry place where the temperature will be between 30 and 120°F.

DO NOT STORE UNITS WITH BATTERIES INSIDE. THIS WILL DAMAGE THEM AND VOID THE WARRANTY.

Distributed by:
Great Lakes IPM, Inc.
10220 Church Rd NE
Vestaburg MI 48891

989-268-5693
800-235-0285
FAX: 989-268-5311

www.greatlakesipm.com
E-mail: glipm@greatlakesipm.com